



## SPECIFICATIONS

Model No.	XFC-02
Number of Fibers	Single
Cladding Diameter	125μm~460μm
Coating Diameter	230μm~600μm
Cleaved Length	2~22mm
Cleaving Angle	Typical 0.5°
Cleaved Method	Applying tension and blade scoring
Blade and Lifetime	Diamond blade, 10 cutting positions* 2000 times per position(125 μm cladding fiber)
Power Supply	Adapter, input: AC100-240V(50/60Hz), output: DC11~13.5V, 3A
Operation Condition	Humidity: 0~95%; Temperature: 0~+40°C(no condensation)
Dimension	197mm(L)×110mm(W)×135mm(H)
Battery	3400mAh, 2 hours for fully charge, continuous working time up to 8 hours(about 600 cores cleaving)
Weight	2.3kg(with battery)

## PACKING

Item	Quantity	Item	Quantity
XFC-02	1pc	Insert LU00(0/200)	1pc
Tools(01/02)	1set	Insert LU01(250/400)	1pc
Power Adapter	1pc	Insert LU02(500/750)	1pc
Power Cord	1pc	Insert LD03(250)	1pc
User Manual(USB drive)	1pc	Insert LD04(400)	1pc
—	—	Insert LD05(500)	1pc



Please understand the above contents are subject to change without prior notice.