

X-97 Handheld FTTx Fusion Splicer



Specially Designed for FTTx/FTTH Projects

- ※ Small and light, easy to carry
- ※ 7 seconds splicing & 26 seconds heating
- ※ Automatic & real-time ARC calibration
- ※ Long time working battery, 250 cycles splicing & heating
- ※ Stable splicing and low splicing loss
- ※ Automatic splicing and heating, easy to operate
- ※ 4.3" touch screen color LCD display
- ※ Apply to bare fiber, pigtails, drop cable etc.
- ※ Suitable for FTTx, FTTH, CATV projects etc.

Specifications

Applicable Fiber	G651/G652/G653/G655/G657 etc.
Cladding Diameter	80~150μm
Coating Diameter	160~3000μm
Cleaved Length	10-16mm(coating diameter<250μm), 16mm(coating diameter: 250~1000μm)
Typical Splice Loss	G651: 0.01dB; G652: 0.02dB; G653: 0.04dB; G655: 0.04dB; G657: 0.02dB
Return Loss	>60dB
Splicing Program	100 modes
Operation Mode	Manual/Auto
Auto-Heating	Available
Splicing Time	7~12 seconds
Heating Time	20~26 seconds for 40mm and 60mm shrinkable sleeves
Fiber Magnification	320X(X or Y view), 160X(X and Y view)
Viewing Display	Dual high sensitivity camera, 4.3" HD color LCD touch screen
Data Storage	8000 groups fusion records
Loss Evaluation	Available
Tension Test	1.8~2.2N
Interface	GUI menu interface, easy for operation
Battery Capacity	Detachable 5200mAh Li-battery , typical 250 cycles splicing and heating
Power Supply	Adapter, input: AC100~240V(50/60Hz), output: DC11~13.5V
Electrode Life	More than 4000 ARC discharges, easy to replace
Terminal	USB 2.0 port, for software upgrading, records exporting
Operating Condition	Altitude: 0~5000m; Humidity: 0~95%; Temperature: -10°C~+50°C; Max wind: 15m/s
Dimension/Weight	160mm(L)×140mm(W)×135mm(H)(including rubber bumper)/2.04kg(with battery)

Package



Please understand the above contents are subject to change without prior notice.